




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : <b>H01R 9/26</b>	<b>A1</b>	(11) International Publication Number: <b>WO 94/18722</b> (43) International Publication Date: <b>18 August 1994 (18.08.94)</b>
<p>(21) International Application Number: <b>PCT/GB94/00290</b></p> <p>(22) International Filing Date: <b>10 February 1994 (10.02.94)</b></p> <p>(30) Priority Data: <b>9302586.4</b>      <b>10 February 1993 (10.02.93)</b>      <b>GB</b></p> <p>(71) Applicant (for all designated States except US): <b>A.C. EGERTON LIMITED [GB/GB]; Murray Road, Leasons Hill, Orpington, Kent BR5 3QU (GB).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): <b>DOOLEY, Andrew, Philip, Charles [GB/GB]; A.C. Egerton Limited, Murray Road, Lessons Hill, Orpington, Kent BR5 3QU (GB).</b></p> <p>(74) Agents: <b>HUTCHINS, Michael, Richard et al.; Fry Heath &amp; Spence, St. Georges House, 6 Yattendon Road, Horley, Surrey RH6 7BS (GB).</b></p>		<p>(81) Designated States: <b>AU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b></p> <p><b>Published</b> <i>With international search report.</i></p>

(54) Title: TRANSMISSION LINE CONNECTORS AND ASSEMBLIES THEREOF



## (57) Abstract

A transmission wire connector includes a first wire contact member and a second wire contact member mounted in bores in a base unit wherein the first and second contact members may slide to make contact with an exchange linked wire, and a consumer linked wire respectively, the first and second wire contacts within the base unit being isolated one from the other; together with a separable module unit capable of coupling with the base unit and providing direct or indirect electrical connection between the first and second contacts when the module unit is coupled to the base unit, the separable module unit being one of a plurality of such module units arranged to provide different functions to the connector or a wire it connects.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

TRANSMISSION LINE CONNECTORS AND ASSEMBLIES THEREOF

This invention relates to transmission wire connectors and assemblies thereof, and more particularly, although not exclusively, to connector assemblies for linking telecommunication wires together, particularly wires from a telecommunications exchange to wires leading to subscribers.

It is known to provide such connectors and assemblies in which a plurality of contacts having wire insulation penetration capability are electrically connected at one end to insulated wires from a telecommunications exchange. Insulated wires leading to the telecommunications subscribers are then electrically connected either directly or indirectly to the other end of the contacts. Commonly such terminals are mounted at the top of an outdoor telecommunication pole and act as distribution points for telecommunication wires to subscribers.

Typically a twenty pair exchange cable is permanently connected to contacts at one level of the assembly, whilst the wires linking the pole top and subscribers premises (commonly referred to as drop wires) are connected, disconnected or reconnected at a separate level of the assembly as may be required from time to time.

It is to be understood that the assembly, although commonly mounted on a telecommunications pole, may also be mounted on the outside wall of the building, in a building service area, or on a lower pedestal mount. It may vary in size typically from 5 to 50 pairs of wires, each pair servicing one piece of equipment (such as a telephone, a fax, or an alternative form of modem).

Connector assemblies of the pole top distribution point (PTDP) kind have traditionally proved a convenient location to hold ancillary equipment such as surge arresters to reduce the damage to plant caused by lightning strikes, and contact between electrical power lines and telephone wires. Technically the main problem with such PTDP assemblies and such ancillary equipment has been to protect the individual components, such as the surge arrester and its housing, from the environment, especially from water contaminated with chemicals such as salt.

It has been proposed to house additional passive, and to introduce active electronic devices to the PTDP. These include, for example, "soft dial tone" components (which enable the wires to be tested even though no subscriber is

connected) and "remote interface devices" (which allow the wire to be tested from exchange to the PTDP and, quite separately, from the PTDP to a subscriber and also allows for disconnection of the subscriber by remote control). Other similar components have been proposed for inclusion in the PTDP.

However, not only does the addition of a multiplicity of function components add to the problems of protection from the environment of the PTDP point and its constituents, but also most seriously can effect the complication of the layout of the assembly if it is to accommodate the various components.

There are in service, 40 year old PTDP and the longevity of modern designs should be even greater than this. Unimaginable advances in electronics will be made in the lifetime of a PTDP but it may not be economically viable to discard existing plant in order to take advantage of new technologies.

It is an object of the present invention to provide a connector and an assembly of connectors which overcomes or at least significantly reduces the above-mentioned difficulties.

In accordance with the present invention there is provided a transmission wire connector including a first wire contact member and a second wire contact member mounted in bores in a base unit wherein the first and second contact members may slide to make contact with an exchange linked wire, and a consumer linked wire

respectively, the first and second wire contacts within the base unit being isolated one from the other; together with a separable module unit capable of coupling with the base unit and providing direct or indirect electrical connection between the first and second contacts when the module unit is coupled to the base unit, the separable module unit being one of a plurality of such module units arranged to provide different functions to the connector or a wire it connects.

The first and second contacts may be of the kind sliding over and gripping the relevant wire and at the same time displacing insulation about the wire to provide good electrical contact with the conductor. The contacts are preferably of the kind carrying bifurcated blades strongly urged together to contact electrically the relevant cables.

The contacts may slide directly in ways formed in the base unit or alternatively may be mounted in carriers which in turn may slide linearly within the base unit. The carrier is particularly advantageous when a plurality of contacts is to be moved by some means of mechanical advantage.

The connector may be sealed such that the totality of base unit and module unit are water repellent or water resistant.

The base unit and the module unit of the connector may be provided with components such as to enable the provision of pairs of first contacts and pairs of second

contacts with pairs of exchange linked wires and user linked wires respectively in accordance with normal practice.

The base unit may include means to provide mechanical advantage in the contact making sliding movement of one or a pair of the contacts with the associated relevant wires. In addition, the exchange wire contact or contacts may be pushed into insulation displacement electrical contact with the exchange wire by manual means upon the coupling of the module unit with the base unit.

The module units may include one having a straightforward electrical connection between the first and second contacts or pairs of contacts, and may include alternative modes of connection therebetween together with additional utility units built in such as a three pole arrester, a soft dial tone test facility, a five pole arrester, a remote interface device, as well as a common earth pole capable of linking through the base unit to earthing contact with and beyond the casing of the connector when in its assembly.

The module may have no contacts, but from an insulating blanking plug which completes the waterproofing of the connector until it is joined to a subscriber.

It is envisaged that modules may be produced in a variety of colours to denote their function, and the function that they bestow upon the connector.

The interface between modules and base unit ideally may include polarising features, the negative (hole) being

on the base unit and if all base units include the polarising feature, and only those modules which are orientation sensitive include the feature, then the system is secure without being unnecessarily restrictive.

The first and second contacts may, at least upon full assembly, be located wholly within the base unit.

A latching arrangement may be provided to ensure that coupling between the module unit and the base unit is secure, and even in some circumstances permanent.

The invention includes within its scope an assembly of connectors as hereunder defined:

The invention will now further be described by way of example with reference to the accompanying drawings in which:-

Figure 1 is a schematic perspective view showing an assembly of connectors in accordance with the invention;

Figure 2 is a sectional schematic view of a base unit of the connector of the present invention in a partially exploded configuration;

Figure 3 shows the base unit of Figure 2 in an assembled condition together with a module unit separated therefrom;

Figure 4 shows a connector in accordance with the invention with a module unit fully coupled to the base unit, and with additional facilities included within the module unit; and

Figures 5(a), (b), (c), (d), and (e) show alternate wiring arrangements in schematic form for the module unit



of a connector as illustrated in Figures 1 to 4.

Figures 6 (a), (b), and (c) illustrate a variation of the embodiment as shown in Figures 2 to 4.

Referring now to the drawings it will be seen from Figure 1 that a plurality of connectors 20 are mounted together within an appropriately sealable elongate box 21 with a sliding lid 22.

In the embodiment of Figures 2 to 4 each connector 20, includes a base unit 1 securable by screw means 2 within its box and supported on a metallic rail 3. The connector has a pair of exchange wire contacts 4 (one shown) which before assembly are each inserted part way into a slot 5 for subsequent engagement by means of closely pressed bifurcations (not shown) at its lower end into insulation splitting electrical contact with a cable (not shown) from the relevant telecommunications exchange which is entered through a port 6.

In addition, a pair of drop wire contacts (one only shown) are provided each for insertion into an appropriate slide bore 8. Before final assembly each contact 7 is left in a partially inserted disposition. Each drop wire contact 7 is engagable with an operating cam 9 to provide mechanical advantage in moving further forward the drop wire contact 7 in its sliding bore 8 so that bifurcations (not shown) at its lower end are enabled to engage and split the insulation on and make electrical contact with a subscriber wire (drop wire) (not shown) entered in through a drop wire port 10. Protection for the drop wire port is

provided by means of a grommet 11 of elastomeric material. An earth contact 12, electrically contacting the metal rail 3 of the connector assembly box passes through an appropriate aperture into a bore 15 through the base unit 1 so that its bifurcated upper end 13 is located level with the upper ends of the exchange contacts 4 and drop wire contacts 7 when completely engaged with their wires on full assembly.

For full assembly of the connector, exchange wires are inserted into ports 6 ready for contact by the exchange contacts 4, and similarly drop wires are inserted into drop wire ports 10. The operating cams 9 are then turned so as to engage fully and make electrical contact between the drop wire contacts and the drop wire after displacing the insulation therearound. Thereafter a module unit 14 is coupled in with the base unit by the contacts 16, 17, 18 thereof, fitting into the appropriate bores 5, 15, 8 respectively of the base unit 1 so that contact 17 engages between the bifurcation of the earth contact 12; contacts 16 engage with the sides and tops of the exchange contacts 4; and contacts 18 engage with the sides of drop wire contacts 7. Thus insertion on coupling of the module unit 14 with the base unit 1 has the effect of causing the appropriate exchange contacts 4 of the base unit 1 to bear upon and engage with the exchange wires located within the exchange wire ports 6, by the bifurcations cutting through and displacing the insulation thereabout to make good electrical contact. At the same

time the central contact of the module unit engages within the bifurcations of the earth contact to provide electrical earthing of any relevant components of the connector module unit. Waterproofing of the coupling between the base 1 and module 14 is assisted by a gel filled labyrinthine groove 23 in the top of the base unit 1.

It will be appreciated that connection, disconnection and reconnection of the drop wire contacts 7 about drop wires can be carried out by means of the operating cams 9 with the module unit 14 in place, the drop wire contacts 7 sliding along the sides of the depending contacts 16 from the module unit 14.

The arrangement illustrated in Figure 4 shows a fully assembled connection in which the module contains a three pole arrester 17, together with a submergible test point 18 comprising a pivoted test contact member located within grease or gel 19 in a side pot 20 to the module unit 14 and movable, by means of an appropriate crocodile clip (not shown) placed about the side of the pot 20 and the side remote therefrom of the upper end of the test contact 19 to bring the lower end thereof into testing engagement with contact bridge 21 within the module between contacts 16 and 18.

The arrangement of the connector of Figures 6(a), (b) and (c) is very similar in principle to that of Figures 2 to 4.

The base unit 1 carries at one side a sleeve 30

downwardly slidable within a bore 31 upon which a module (not shown) may be mounted for connection to contacts 4 and 7, the downward movement of the sleeve on connection sliding contact 4 into slot 5 and contact with exchange wire 32 (as seen in Figure 6(b)).

Movement of contact 7 within its bore 8, instead of by means of a cam is now by means of a screw member 33 having threads 34 engaging in a threaded bore 35 in the base member 1 and connected to a carrier body 37 carrying the bore 8 and port 10 for drop wire 36.

Rotation of the screw member 33 in a clockwise direction within bore 35 of the base 1, lowers carrier body 37 slidably relative to the base member 1 so that the drop wire 36 is engaged by contact 7 which moves within slot 8 (as seen in Figure 6(c)).

Rotation of the screw member 33 thereafter in an anticlockwise direction will disconnect contact 7 from drop wire 36. Both connection and disconnection can be effected whether or not the module (not shown) is connected.

Figures 5(a), (b), (c), (d) and (e) illustrate schematically examples of connection and functions which can be accommodated within the module unit 14.

Thus Figure 5(a) shows a simple unprotected twin contact arrangement without connection to the earth pin.

This connects the exchange wire contacts to the drop wire contacts without any additional circuitry or function.

Figure 5(b) shows circuitry for a 3 pole arrestor and Figure 5(d) the circuitry for a 5 pole arrestor. It can be seen that alternatively two single pole arrestor might have been fitted into a module. It would be possible to use carbon spark gaps or a solid state devices as alternatives to Gas Discharge Tubes which are the most common form of over voltage protection in this application.

The over current protection in the 5 pole arrestor could be provided by a fusible link or a positive temperature coefficient thermistor.

Figure 5(c) shows a unit that might be fitted as the connector is shipped to the customer. It incorporates line termination circuitry, the purpose of which is to allow the wires and connections between the exchange and the PTDP to be tested before the drop; wires and the subscriber are connected to the system. Without this device, before the subscriber is connected the circuit is open at the PTDP and thus only limited testing from the exchange is possible.

A scheme for a remotely controlled switch and test unit is shown in Figure 5(e). The circuitry would typically be controlled by a (coded) signal from the exchange.

Such a signal could cause the links between exchange wire contacts and drop wire contacts to be broken.

With these links broken it is thus possible to test

the circuit between the exchange and the PTDP.

A further (coded) signal from the exchange to the circuitry in this device would cause the circuit between the PTDP and the subscriber to be tested, the result of such testing being signalled back to the exchange.

Upon completion of testing, the link between exchange wire contacts and drop wire contacts would be remade.

The beneficial functioning of the connector according to the invention illustrated and described is manifold, including the following features:-

(a) Making connection to exchange side contacts.

This connection that is made when the connector is installed, often to a small (0.4mm to 0.63mm) conductor insulated with solid polyethylene. This insulation displacing contact is held within the base unit body. The unit may be shipped to the user with the contact positioned, and held by friction or detent, in a retracted position. After the exchange wires have been passed into the ports, the contacts may be pushed forward by finger force on the module to make connection.

(b) Making connection to drop wires. This is a connection that may be made and broken dozens of times in the life of the connector. These disturbances may happen due to change of subscribers requirements or damage to drop wire (such as trees, power lines, high vehicles).

Drop wires often range in size and materials from 0.5mm to 1.14mm diameter conductors that may be of copper, cadmium copper or copper covered steel and insulation, 1-

0mm to 5.5mm overall dimension, that may be polyethylene, polyvinyl chloride or (butyl) rubber.

The drop wire contacts are contained wholly within the base unit. These are insulation displacing contacts. Because of the high forces (up to 500N) required to push these contact on to the large drop wires, an operating mechanism (which may be driven by screwdriver or hexagon socket) is used. This operating mechanism is built entirely into the base unit.

(c) Earth connection. Wholly contained with the base unit is a metallic element or contact, which at one end effects a connection within the module unit and at the other with an earth bus or rail built into the terminal box or enclosure.

(d) Joining exchange side terminal to drop wire terminal, is performed by a link means built into the module unit. The link in its simplest form may be a single piece of copper alloy for each line. There may be a mechanical or electronic switch built into the link in order to sever the service to the subscriber.

(e) Waterproofness. The exchange connection is readily sealable with a petroleum grease. This allows entry of the insulated wire, but stops water reaching the terminal along the exchange wire port.

The Drop Wire connection is sealable by a re-usable sealant system, This may comprise a petroleum grease as used in the exchange side plus an elastic grommet wiper to help retain the grease in the Drop Wire ports when the

drop wire is removed.

The module to base unit interface may include a reusable seal that is not readily contaminated. There are many possible configurations of fluid, gel-like and elastic seal.

By means of the invention we have provided a connector and assembly of connectors of simple but great diverse capability for use primarily in the telecommunications industry.

It is to be understood that the foregoing is merely exemplary of connectors and assemblies for connectors in accordance with the invention and that modifications can readily be made thereto without departing from the true scope of the invention.



Claims

1. A transmission wire connector including a first wire contact member and a second wire contact member mounted in bores in a base unit wherein the first and second contact members may slide to make contact with an exchange linked wire, and a consumer linked wire respectively, the first and second wire contacts within the base unit being isolated one from the other; together with a separable module unit capable of coupling with the base unit and providing direct or indirect electrical connection between the first and second contacts when the module unit is coupled to the base unit, the separable module unit being one of a plurality of such module units arranged to provide different functions to the connector or a wire it connects.

2. A transmission wire connector as claimed in Claim 1 wherein the first and second contacts are of the kind sliding over and gripping the relevant wire and at the same time displacing insulation about the wire to provide good electrical contact with the conductor.

3. A transmission wire connector as claimed in Claim 1 or 2 wherein the contacts are of the kind carrying bifurcated blades strongly urged together to contact electrically the relevant cables.

4. A transmission wire connector as claimed in any one of the preceding claims, the connector being sealed such that the totality of the base unit and the module unit are water repellent or resistant.

5. A transmission wire connector as claimed in any one of the preceding claims wherein at least one of the first wire contact member and the second wire contact member is capable of sliding within its bore for connections to, disconnection from, and reconnection to, its associated exchange or consumer linked wire.

6. A transmission wire connector as claimed in any one of the preceding claims where at least one of the wire contact members is capable of connection with the associated relevant link wire with a module connected to the base unit.

7. A transmission wire connector as claimed in any one of the preceding claims wherein the base unit includes means to provide mechanical advantage in the contact making sliding movement of at least one of the wire contact members with the associated relevant link wires.

8. A transmission wire connector as claimed in Claim 7 wherein the exchange wire contact or contacts are pushed into insulation displacement electrical contact with the exchange wire by manual means upon the coupling of the

module unit with the base unit.

9. A transmission wire connector as claimed in any one of the preceding claims wherein the base unit and the module unit thereof is provided with components such as to enable the provision of pairs of the first contact members and pairs of the second contact members with pairs of exchanged link wires and user link wires respectively.

10. A transmission wire connector as claimed in any one of the preceding claims wherein a module unit includes a direct or straight forward electrical connection between the first and second contact or pairs of contacts.

11. A transmission wire connector as claimed in Claim 1 to 8 wherein a module unit includes at least one of a plurality of options of modes of connection therebetween together with at least one additional utility units incorporated therein.

12. A transmission wire connector as claimed in Claim 11 wherein an additional utility unit comprises a three pole arrester.

13. A transmission wire connector as claimed in Claim 11 wherein an additional utility unit is a soft dial term facility.

14. A transmission wire connector as claimed in Claim 11 wherein an additional utility unit is a five pole arrester.

15. A transmission wire connector as claimed in Claim 11 wherein an additional utility unit is a remote interfaced device.

16. A transmission wire connector as claimed in any one of Claims 11 to 15 wherein a module unit includes a common earth pole capable of linking through the base unit to earthing contact with and beyond the casing of the connector when disposed in its assembly.

17. A transmission wire connector as claimed in any one of the preceding claims wherein the first and second contacts are, upon full assembly of the connector, located wholly within the base unit.

18. A transmission wire connector as claimed in any one of the preceding claims wherein a latching arrangement is provided to ensure that the coupling between the module unit and the base unit is secure and/or permanent.


19. A transmission wire connector as claimed in Claim 18 wherein the coupling facility between the module unit and the base unit is such that coupling is only possible in one relative disposition between the two units.

20. An assembly of transmission wire connectors as claimed in any one of the preceding claims.

21. A transmission wire connector as disclosed in and as hereinbefore described with reference to the accompanying drawings.

22. An assembly of transmission wire connectors substantially as shown in and as hereinbefore described with reference to the accompanying drawings.


1/6





SUBSTITUTE SHEET.

2/6

FIG. 2.



SUBSTITUTE SHEET





4/6

FIG. 5(a)




FIG. 5(b)




FIG. 5(c)




FIG. 5(d)






FIG. 5(e)



5/6

FIG. 6(a)



SUBSTITUTE SHEET.

6/6

FIG. 6(b)





FIG. 6(c)



SUBSTITUTE SHEET

## INTERNATIONAL SEARCH REPORT

Inventor's Application No  
PCT/GB 94/00290A. CLASSIFICATION OF SUBJECT MATTER  
IPC 5 H01R9/26

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 5 H01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO,A,92 15129 (RAYCHEM LIMITED) 3 September 1992  see page 17, line 17 - page 18, line 2; figure 12 ---	1-3,6,7, 9,10,17, 20-22
A	US,A,5 149 278 (WAAS ET AL.) 22 September 1992 see abstract; figure 2B ---	1-4
A	EP,A,0 315 345 (NORTHERN TELECOM LIMITED) 10 May 1989 see column 7, line 31 - line 46; figure 8 ---	1-3
A	GB,A,2 176 062 (A.C. EGERTON LIMITED) 10 December 1986 see page 1, line 123 - page 2, line 20; figure 2 -----	1-3,12, 14

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z" document member of the same patent family

Date of the actual completion of the international search

20 May 1994

Date of mailing of the international search report

27 MAI 1994

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Kohler, J

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter

Application No

PCT/GB 94/00290

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9215129	03-09-92	AU-A- 1193892 CN-A- 1064569 EP-A- 0573442	15-09-92 16-09-92 15-12-93
US-A-5149278	22-09-92	AU-A- 1578592 EP-A- 0572572 WO-A- 9215130	15-09-92 08-12-93 03-09-92
EP-A-0315345	10-05-89	CA-A- 1298369 DE-A- 3877328 JP-A- 1154471 US-A- 4826449	31-03-92 18-02-93 16-06-89 02-05-89
GB-A-2176062	10-12-86	NONE	

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**